# **SAFETY DATA SHEET**



# BestScent Smoke & Odor Eliminator

# **Section 1. Identification**

Product identifier : BestScent Smoke & Odor Eliminator

Product code : 062

Other means of : Not available. identification

Product type : Liquid.

# Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Deodorizer		
Uses advised against	Reason	
For Industrial and Institutional Use Only	_	

Supplier's details : Betco Corporation

1690 Huron Church Road, Suite 169

Windsor ON N9C0AC CA

400 Van Camp Road

Bowling Green, OH 43402 US

www.betco.com 888-462-3826

Emergency telephone number (with hours of operation) : Chemtrec (800) 424-9300 24 hour

# Section 2. Hazard identification

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SKIN SENSITIZATION - Category 1
ASPIRATION HAZARD - Category 1

**GHS label elements** 

Hazard pictograms :









Signal word : Danger

**Hazard statements** : Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

**Precautionary statements** 

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 1/12

# Section 2. Hazard identification

u	-	10	2	$\overline{}$	n
_	re۱	76	HU	ıv	•

: Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Avoid breathing vapor. Contaminated work clothing should not be allowed out of the workplace. Do not pierce or burn, even after use.

### Response

: IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention.

#### **Storage**

: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

#### **Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

# Supplemental label elements

: Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 22%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 22%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 7%

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

Ingredient name	% (w/w)	CAS number
Petroleum refining, hydrotreated light distillate	5 - 10	64742-47-8
propane	1 - 5	74-98-6
Naphtha (petroleum), hydrotreated heavy	1 - 5	64742-48-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First-aid measures

# **Description of necessary first aid measures**

#### Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

### **Inhalation**

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 2/12

# Section 4. First-aid measures

## Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion** : May be fatal if swallowed and enters airways.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

media

Unsuitable extinguishing

media

: None known.

# Specific hazards arising from the chemical

: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 3/12

# Section 5. Fire-fighting measures

# **Hazardous thermal** decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

# **Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

# **Special protective** equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

# Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 4/12

# Section 7. Handling and storage

### **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not swallow. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, : including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
Petroleum refining, hydrotreated light distillate	CA British Columbia Provincial (Canada, 7/2018). Absorbed through skin.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Alberta Provincial (Canada, 6/2018).  Absorbed through skin.  8 hrs OEL: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Ontario Provincial (Canada, 1/2018).  Absorbed through skin.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.
propane	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m³ 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 1000 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 5/12

# Section 8. Exposure controls/personal protection

TWA: 1000 ppm 8 hours.
CA British Columbia Provincial (Canada, 7/2018). Oxygen Depletion [Asphyxiant].
Explosive potential.

Appropriate engineering controls

**Environmental exposure** controls

- : The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 6/12

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color Clear. Odor : Pleasant. **Odor threshold** : Not available. pН : Not available. : Not available. **Melting point Boiling point** : Not available.

: Closed cup: -104.4°C (-155.9°F) Flash point

**Evaporation rate** Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

: Not available. Vapor pressure Vapor density : Not available. **Relative density** : Not available.

Solubility : Partially soluble in the following materials: cold water and hot water.

Not available. Solubility in water Partition coefficient: n-: Not available.

octanol/water

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available. : Not available. **Viscosity** : Not available. Flow time (ISO 2431)

**Aerosol product** 

Type of aerosol : Spray **Heat of combustion** : 8.188 kJ/g

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** : Not available.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 7/12

# **Section 11. Toxicological information**

# **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Naphtha (petroleum), hydrotreated heavy	LC50 Inhalation Vapor	Rat	8500 mg/m³	4 hours
	LD50 Oral	Rat	>6 g/kg	-

# **Irritation/Corrosion**

Not available.

### **Sensitization**

Not available.

#### Mutagenicity

Not available.

### **Carcinogenicity**

Not available.

# **Reproductive toxicity**

Not available.

### **Teratogenicity**

Not available.

# Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
propane	Category 3	Not applicable.	Respiratory tract irritation

# Specific target organ toxicity (repeated exposure)

Not available.

# **Aspiration hazard**

Name	Result
Petroleum refining, hydrotreated light distillate	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely

routes of exposure

: Routes of entry anticipated: Dermal, Inhalation.

Routes of entry not anticipated: Oral.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 8/12

# **Section 11. Toxicological information**

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : N

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

**Potential immediate** 

Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

Not available.

# **Section 12. Ecological information**

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Petroleum refining, hydrotreated light distillate	Acute LC50 2200 μg/l Fresh water	Fish - Lepomis macrochirus	4 days

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
propane Naphtha (petroleum), hydrotreated heavy	1.09	- 10 to 2500	low high

Date of issue/Date of revision: 9/8/2021Date of previous issue: 12/22/2020Version: 2.019/12

# Section 12. Ecological information

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

## **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	TDG Classification	DOT Classification	ADR/RID	IMDG	IATA
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	Aerosols, Flammable	Aerosols, Flammable	Aerosols, Flammable	Aerosols	Aerosols, Flammable
Transport hazard class(es)	2.1	2.1	2	2.1	2.1
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

### **Additional information**

**TDG Classification** 

: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.13-2.17 (Class 2).

**DOT Classification** 

: Limited quantity Yes.

ADR/RID

Tunnel code (D)

**IMDG** 

: Limited quantity Yes.

IATA

: Limited quantity Yes.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of issue/Date of revision : 9/8/2021 : 12/22/2020 Version : 2.01 10/12 Date of previous issue

# **Section 14. Transport information**

Transport in bulk according : Not available.

to Annex II of MARPOL and

the IBC Code

# **Section 15. Regulatory information**

# **Canadian lists**

Canadian NPRI : The following components are listed: Butane (all isomers); hydrotreated light

distillate; propane; hydrotreated heavy naphtha

**CEPA Toxic substances**: None of the components are listed.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

**Inventory list** 

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

**Europe** : Not determined.

Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined

New Zealand : Not determined.

**Philippines** : All components are listed or exempted.

Republic of Korea : Not determined.

**Taiwan** : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

**United States** : All components are listed or exempted.

Viet Nam : Not determined.

# Section 16. Other information

**History** 

Date of printing : 9/8/2021

Date of issue/Date of : 9/8/2021

revision

Date of previous issue : 12/22/2020

Version : 2.01

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 11/12

# **Section 16. Other information**

### Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

HPR = Hazardous Products Regulations

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas SKIN SENSITIZATION - Category 1 ASPIRATION HAZARD - Category 1	Expert judgment On basis of test data Expert judgment Expert judgment

References : Not available.

▼ Indicates information that has changed from previously issued version.

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 9/8/2021 Date of previous issue : 12/22/2020 Version : 2.01 12/12