### **SAFETY DATA SHEET**

EasyStreet Super Matte



### **Section 1. Identification**

Product identifier : EasyStreet Super Matte

Product code : B1658

Other means of : Not available.

Product type : Liquid.

identification

### Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Floor Finish		
Uses advised against	Reason	
For Professional Use Only	-	

Supplier's details : Basic Coatings

1690 Huron Church Road, Suite 169

Windsor ON N9C0AC CA

400 Van Camp Road

Bowling Green, Ohio 43402 US

www.basiccoatings.com

(800) 441-1934

Emergency telephone number (with hours of operation)

: Chemtrec (800) 424-9300

24 hour

### Section 2. Hazard identification

Classification of the substance or mixture

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

TOXIC TO REPRODUCTION (Unborn child) - Category 1

**GHS label elements** 

Hazard pictograms





Signal word : Danger

**Hazard statements** : Causes serious eye irritation.

Causes skin irritation.

May damage the unborn child.

**Precautionary statements** 

**Prevention**: Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves. Wear protective clothing: Recommended: Protective gloves. Wear eye or face protection: Recommended:

safety glasses. Wash hands thoroughly after handling.

Response : IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of

soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists: Get medical attention.

EasyStreet Super Matte

### Section 2. Hazard identification

Storage

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Section 3. Composition/information on ingredients

Substance/mixture
Other means of
identification

: Not available.

: Mixture

Ingredient name	% (w/w)	CAS number
Polyurethane	60 - 80	proprietary
N-methyl-2-pyrrolidone	1 - 5	872-50-4
(2-methoxymethylethoxy)propanol	1 - 5	34590-94-8
N-ethyl-2-pyrrolidone	1 - 5	2687-91-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation.

**Ingestion**: No known significant effects or critical hazards.

Over-exposure signs/symptoms

### Section 4. First-aid measures

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

### For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

### Occupational exposure limits

Ingredient name	<b>Exposure limits</b>
N-methyl-2-pyrrolidone	CA Ontario Provincial (Canada, 1/2018).
	TWA: 400 mg/m³ 8 hours.
(2-methoxymethylethoxy)propanol	CA Alberta Provincial (Canada, 4/2009).
	Absorbed through skin.
	8 hrs OEL: 100 ppm 8 hours.
	15 min OEL: 909 mg/m³ 15 minutes.
	8 hrs OEL: 606 mg/m <sup>3</sup> 8 hours.
	15 min OEL: 150 ppm 15 minutes.
	CA British Columbia Provincial (Canada,
	6/2017). Absorbed through skin.
	TWA: 100 ppm 8 hours.
	STEL: 150 ppm 15 minutes.
	CA Quebec Provincial (Canada, 1/2014).
	Absorbed through skin.
	TWAEV: 100 ppm 8 hours.
	TWAEV: 606 mg/m <sup>3</sup> 8 hours.
	STEV: 150 ppm 15 minutes.
	STEV: 909 mg/m³ 15 minutes.
	CA Ontario Provincial (Canada, 1/2018).
	Absorbed through skin.
	STEL: 150 ppm 15 minutes.
	TWA: 100 ppm 8 hours.
	CA Saskatchewan Provincial (Canada,
	7/2013). Absorbed through skin.
	STEL: 150 ppm 15 minutes.
	TWA: 100 ppm 8 hours.

## Appropriate engineering controls

**Environmental exposure** 

- : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

controls

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: safety glasses

# **Skin protection Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## Section 8. Exposure controls/personal protection

Body protection : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product. Recommended: Protective gloves

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

### Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.

Color : Opaque. Off-white.

Odor : Mild. Aromatic.

Odor threshold : Not available.

**pH** : 7.5 to 9

Melting point: Not available.Boiling point: Not available.

Flash point : Closed cup: >120°C (>248°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.
Relative density : 1.05333

**Solubility** : Very slightly soluble in the following materials: cold water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

**Incompatible materials**: Not available.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
N-methyl-2-pyrrolidone	LD50 Dermal	Rabbit	8 g/kg	-
	LD50 Oral	Rat	3914 mg/kg	-
N-ethyl-2-pyrrolidone	LD50 Oral	Rat	1350 mg/kg	-

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
N-methyl-2-pyrrolidone	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
(2-methoxymethylethoxy) propanol	Eyes - Mild irritant	Human	-	8 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
N-ethyl-2-pyrrolidone	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-

### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal. Routes of entry not anticipated: Inhalation.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation.

**Ingestion**: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

### **Section 11. Toxicological information**

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.

**Teratogenicity** : May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.Fertility effects : No known significant effects or critical hazards.

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Route	ATE value
Oral	70208.2 mg/kg

### **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
N-methyl-2-pyrrolidone	Acute LC50 1.23 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 832 ppm Fresh water	Fish - Lepomis macrochirus	96 hours

#### Persistence and degradability

Not available.

### **Bioaccumulative potential**

EasyStreet Super Matte

### **Section 12. Ecological information**

Product/ingredient name	LogPow	BCF	Potential	
N-methyl-2-pyrrolidone	-0.46	-	low	
(2-methoxymethylethoxy)	0.004	-	low	
propanol				
N-ethyl-2-pyrrolidone	-0.2	-	low	

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	TDG Classification	DOT Classification	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

: Not available.

### Section 15. Regulatory information

**Canadian lists** 

Canadian NPRI : The following components are listed: N-Methyl-2-pyrrolidone

**CEPA Toxic substances**: None of the components are listed.

International regulations

**Chemical Weapon Convention List Schedules I, II & III Chemicals** 

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

**Inventory list** 

Australia : At least one component is not listed.

Canada : At least one component is not listed.

China : Not determined.

Europe : Not determined.

Japan : Japan inventory (ENCS): At least one component is not listed.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

New Zealand : At least one component is not listed.

Philippines : At least one component is not listed.

Republic of Korea : At least one component is not listed.

Taiwan : Not determined.
Thailand : Not determined.
Turkey : Not determined.
United States : Not determined.
Viet Nam : Not determined.

### Section 16. Other information

**History** 

Date of printing : 10/7/2019

Date of issue/Date of : 10/7/2019

revision

Date of previous issue : No previous validation

Version : 1

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

HPR = Hazardous Products Regulations

EasyStreet Super Matte

### Section 16. Other information

### Procedure used to derive the classification

Classification	Justification
SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION (Unborn child) - Category 1	Calculation method Calculation method Calculation method

References : Not available.

▼ Indicates information that has changed from previously issued version.

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.